

# EntryProx™ Reader

125 kHz Proximity

Stand-Alone, Single-Door Proximity Reader • 4045

- ▶ **Ideal for Unique Applications** - Proximity access control for small installations or remote locations.
- ▶ **Trouble-Free Keypad Input** – Extra secure keypad enables PIN entry or programming.
- ▶ **Remote Monitoring** - Configurable to be used in conjunction with an on-line system.



**ACCESS independence.**

## Key Features

- ▶ **Faster Programming** - Batch load up to 2,000 HID cards or keytags with a single keypad command sequence.
- ▶ **Efficient Badge Administration** - Block Delete allows deletion of cards/keytags by user location.
- ▶ **Increased Reporting Flexibility** - Utilize hand held data transfer device to download transactions and card database.

HID's EntryProx™ stand-alone reader truly stands alone in what it delivers. Compatible with all HID proximity cards and keytags, EntryProx™ provides single-door proximity access control and is ideal for unique applications. The reader, designed to be weather- and vandal-resistant, can be mounted indoors or outdoors up to 10 feet away from the control unit using the detachable antenna module. The versatile, attractive unit is easily modified to become an on-line reader by switching to Wiegand output mode, allowing it to connect to any OEM controller and provide card and PIN output.

The ADA-compliant 12-position keypad features large white-on-black numbers, enabling PIN entry or programming, with optional audio feedback and a raised dot on the 5 key. For extra security, EntryProx's keypad incorporates the "invalid PIN" lockout feature, preventing unauthorized trial-and-error PIN code entry.

The reader also features faster programming, enabling end-users to batch load up to 2,000 HID cards or keytags, in any format up to 37 bits, by entering a single keypad command sequence. A Block Delete feature allows for efficient badge administration by deleting a sequential range of cards/keytags from the EntryProx by user location. Additionally, the Data Transfer Device (DTD) handled accessory increases reporting flexibility by enabling users to download transactions and card databases by communicating with the EntryProx utilizing an infrared interface.

Customers can select the HID EntryProx Reader with confidence because HID offers a lifetime product warranty and global technical support.

# Specifications

<b>Monitor Inputs</b>	Door Position - N.O. dry contact Request to Exit - N.O. dry contact  *Depending on local installation conditions.
<b>Sounder</b>	4000Hz, defeatable
<b>Relay Outputs</b>	Strike Relay - Form C, switches up to 1A @ 30 VDC Aux Relay - Form C, switches up to 1A @ 30 VDC
<b>LEDs</b>	Bi-Color (Red/Green), Amber, Infrared (use with Data Transfer Device (DTD) accessory)
<b>Cable Distance</b>	Remote Reader Module - 10 feet (3 m) Wiegand Interface - 500 feet (152 m) Recommended cable is ALPHA 1295C (22AWG) 5-conductor stranded with overall shield or equivalent

**Operation**  
Strike Time: 1 - 99 seconds (Adjustable)  
Strike Mode: Access Timer or Toggle/Latch  
Door Ajar Time: 10 - 990 Seconds (Adjustable)

**Card Programming**  
26-bit format - batch enrollment  
Other formats - present card to enroll

**Facility Code Processing Options (26-bit only)**  
Check Facility Code and Card ID  
Check Facility Code only (accept any ID#)

**Unbeatable Warranty and Technical Support**  
Customers can select the HID EntryProx® Reader with confidence because HID offers a lifetime product warranty and 24x7 global technical support.

<b>Read Ranges:*</b>	
<b>ISOProx® II card</b>	Up to 2.5" (6.35 cm)
<b>Smart ISOProx® II</b>	Up to 2.5" (6.35 cm)
<b>HID Proximity &amp; MIFARE® Card</b>	Up to 2.5" (6.35 cm)
<b>HID Proximity &amp; iCLASS® Card</b>	Up to 2.5" (6.35 cm)
<b>ProxKey™ II keyfob</b>	Up to 1.5" (3.8 cm)
<b>ProxCard® II card</b>	Up to 3.0" (7.6 cm)
<b>DuoProx® II card</b>	Up to 2.5" (6.35 cm)
<b>Smart DuoProx® II</b>	Up to 2.5" (6.35 cm)
<b>ProxCard® Plus card</b>	Up to 1.0" (2.5 cm)
<b>Microprox® Tag</b>	Up to 2.0" (5.1 cm)
<b>Mounting</b>	Mounts on US or EU single gang box, wall surface, or on glass with included adhesive pads
<b>Dimensions</b>	5.25" x 2.75" x 1.625" (13.33 cm x 6.98 cm x 4.1 cm)
<b>Power Supply / Current Requirements</b>	10 - 15 VDC, reverse voltage protected Linear supply recommended, 150 mA @ 12 VDC
<b>Operating Temperature</b>	-31° to 150°F (-35° to 66°C)
<b>Operating Humidity</b>	5% to 95% relative humidity non-condensing
<b>Transmit Frequency</b>	125 kHz
<b>Environmental</b>	IP55
<b>Certifications</b>	UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS
<b>Base Part Number</b>	EntryProx 4045CGNU0 EntryProx plus 10 Keytags 4045CGKU0 EntryProx plus 20 ProxCard II 4045CGCU0
<b>Options</b>	Color - Gray Various options are user programmable – not ordered by model. Accessories Security Tool 04-0001-03 Data Transfer Device (DTD) 4045-DTD
<b>Warranty</b>	Warrantied against defects in materials and workmanship for life (See complete warranty policy for details).

\*Dependent upon installation conditions.

© 2009 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 10/2009

MKT-ENTRYPROXC\_DS\_EN

[hidglobal.com](http://hidglobal.com)



**ACCESS experience.**

**HID Global Offices:**

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Phone: (800) 237-7769  
Phone: (949) 732-2000  
Fax: (949) 732-2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160-9800  
Fax: +852 3160-4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Phone: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill  
Suffolk  
CB9 7AE  
England  
Phone: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840